

LC-SSX1 Heat Exchanger




- One piece tube construction eliminates epoxy joints and dissimilar metals in the liquid loop.
- Tubing is made of 316 stainless steel tubing which permits use with a wide variety of liquids.
- Aluminum base plate provides high heat conduction.
- 3/8 inch (9.65 mm) OD tubing accepts a wide variety of compression fittings.
- Can be used with a standard cold plate cooler. Through-holes are located for mounting directly to the CP-061HT, CP-065, CP-110, CP-121HT, CP-130HT, or for mounting one or two directly to the CP-200HT or CP-200HT-TT cold plate coolers.
- RoHS compliant.

TE  [®]
TECHNOLOGY, INC.

Expert Engineering, Precision Manufacturing:
Quality Thermal Solutions Delivered

<https://tetech.com/> • cool@tetech.com • 231-929-3966 • 1590 Keane Drive • Traverse City, MI 49696



NOTE: ALL DIMENSIONS IN MILLIMETERS

A 3D PDF, .stp, and .x_t solid models are also available from the website.

- **Maximum fluid pressure: 1034 kPa**
- **Weight: 0.46 kg**
- **If you intend to mount the LC-SSX1 to a TE Technology, Inc. standard cold plate cooler, an M4 x 0.7 20 mm long screw with an M4 washer is recommended. Use 4 screws and torque each screw to 1.3 N-m. Use thermal grease or other suitable thermal interface material between the cold plate and LC-SSX1.**
- **Please review the [Thermoelectric Cooling Assembly \(TCA\) Instruction Manual](#) (or [manual in other languages](#)), [ordering information](#), and [FAQ's](#) for related technical information before purchasing or using this product.**

If you intend to use a fluid other than water with the LC-SSX1, consult with TE Technology, Inc. for further design assistance. You should also verify fluid compatibility with 316L stainless steel and with any associated fittings.

The LC-SSX1 should be oriented so that if a leak were to occur, fluid would spray/drain away from electrical contact points.

Water expands when freezing! Do not allow water or other similarly behaving fluids to freeze in the LC-SSX1; otherwise, damage could result.



TE TECHNOLOGY, INC.®

Expert Engineering, Precision Manufacturing:
Quality Thermal Solutions Delivered

<https://tetech.com/> • cool@tetech.com • 231-929-3966 • 1590 Keane Drive • Traverse City, MI 49696

LC-SSX1 Performance using Water

(at various inlet temperatures)



NOTE: The calculated thermal resistance curve is based on the assumption that the heat load is evenly spread across the plate surface.



Expert Engineering, Precision Manufacturing:
Quality Thermal Solutions Delivered

<https://tetech.com/> • cool@tetech.com • 231-929-3966 • 1590 Keane Drive • Traverse City, MI 49696


Thermal Performance when used with Standard Cold Plate Coolers

The calculated performance curves below are based on the LC-SSX1 being mounted to a TE Technology standard cold plate cooler. The following assumptions apply:


1. Thermal grease, TP-1, (see accessories at <http://tetech.com/>) is used between the cold plate and the LC-SSX1 (0.04 mm thick layer)
2. Water is flowing at 1.6 L/min through the LC-SSX1

Please also note that the dashed lines on certain portions of the graph represent points where the cooler should not be operated. Otherwise, damage to the cooler could result.


CP-061HT with LC-SSX1



CP-065 with LC-SSX1




CP-110 with LC-SSX1




Expert Engineering, Precision Manufacturing:
Quality Thermal Solutions Delivered

<https://tetech.com/> • cool@tetech.com • 231-929-3966 • 1590 Keane Drive • Traverse City, MI 49696


CP-121HT with LC-SSX1




CP-130HT with LC-SSX1



CP-200HT with One LC-SSX1



CP-200HT with Two LC-SSX1



Expert Engineering, Precision Manufacturing:
Quality Thermal Solutions Delivered

<https://tetech.com/> • cool@tetech.com • 231-929-3966 • 1590 Keane Drive • Traverse City, MI 49696